

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
13 January 2005 (13.01.2005)

PCT

(10) International Publication Number  
**WO 2005/003599 A1**

(51) International Patent Classification<sup>7</sup>: **F16H 48/30**

(21) International Application Number:  
PCT/IB2003/003049

(22) International Filing Date: 4 July 2003 (04.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: SAMUEL, Abraham [IL/IT]; Via Lanzone, 7,  
I-20123 Milano (IT).

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(74) Agent: FIAMMENGHI-DOMENIGHETTI, Delfina;  
Fiammenghi-Fiammenghi, Via San Gottardo, 15, CH-6900  
Lugano (CH).

Published:  
— with international search report

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: DIFFERENTIAL FOR MOTOR VEHICLES WITH DEVICE FOR LOCKING THEREOF



(57) Abstract: A differential (1) for motor vehicles installed between two half-shafts (2, 3) on which two drive wheels are keyed is described, said differential comprising a box (4) driven by the engine by means of 5 the connecting means (5) which cause it to rotate about the axes (L-L) of the half-shafts (2, 3), on the free ends of the latter there being keyed two bevel gears (6, 7) housed inside the box (4), and the differential (1) and the half-shafts (2, 3) being contained inside a casing (8). In this differential (1) each of the flanges (9, 10) through which the half-shafts (2, 3) penetrate into the box (4) has a cylindrical extension (11) outwards, at least one cavity (14) formed in a sleeve (15) slidable coaxially on each half-shaft (3) and rotationally locked thereto, mounted inside the said casing (8) and provided with means (16) which cause it to slide in the two directions (A, B) causing engagement between the grooves (12i, 13i) or disengagement thereof, locking together the box (4) and the half-shafts (2, 3) or performing disengagement thereof.

WO 2005/003599 A1